Revision: 4 October 2009

SDS No. V161500030

Version number: 1

Page 1 of 7



#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1	Product identifier	ENEOS PREMIUM HYPER 5W30
1.2	Use	Synthetic engine oil.
1.3	Details of the supplier of	JX Nippon Oil & Energy Europe Limited.
	the safety data sheet	4th Floor, 4 Moorgate, London EC2R 6DA, U.K.
1.4	Telephone number	+44-20-7186-0400
1.5	FAX number	+44-20-7186-0419

#### **2 HAZARDS IDENTIFICATION**

Classification system	: The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
Hazard classification	: This preparation is not classified as dangerous according to Directive 1999/45/EC as amended and adapted.
Other hazards	
Human health hazards	: Prolonged or repeated contact may cause skin to become dry or cracked.
Physical/chemical hazards	: None.
Environmental hazards	: This product floats on water and may affect the oxygen-balance in the water.
Primary route of exposure	: Skin and eyes contact.
Effects and symptoms	
- Inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
- Skin contact	<ul> <li>Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.</li> <li>High-pressure injection under skin may cause serious damage.</li> </ul>
- Eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
- Ingestion	: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
Note	: USED ENGINE OILS: Used engine oil may contain hazardous components which have the potential to cause skin cancer.See Toxicological Information, section 11 of this Safety Data Sheet.

### **3 COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Preparation

: Preparation.

Revision: 4 October 2009

SDS No. V161500030

Version number: 1

Page 2 of 7



#### **3 COMPOSITION/INFORMATION ON INGREDIENTS (continued) Chemical characterization** : Chemically modified base oil and proprietary performance additives. : This product is not hazardous but contains hazardous components. Components Composition Substances presenting a health or environmental hazard within the meaning of Directive 67/548/EEC / Substances for which there are Community workplace exposure limits : Classification Substance name Conc. (wt%) CAS No EC No Annex No Between 0.1 and 1 % 68649-42-3 272-028-3 Xi; R38-41 N; R51-53 Zinc alkyl dithiophosphate Between 0.1 and 1 % Xi; R38 Zinkalkylditiofosfat 68649-42-3 272-028-3 -----N; R51-53 T: R23/24/25 Diphenylamine Between 0.1 and 1 % 122-39-4 204-539-4 612-026-00-5 R33 N; R50-53 Xn: R62 p-Dodecylphenol Between 0.1 and 1 % 310-154-3 Xi; R38 N; R50-53 Other information : Occupational Exposure Limit(s), if available, are listed in section 8. The base oil contains less than 3% DMSO-extract measured according IP 346, therefor it is NOT classified as T/R45: "May cause cancer" (Note L). **Text of R-Phrases** : See Heading 16. **4 FIRST AID MEASURES** - General information : Seek medical attention if ill effect develops. - Inhalation : Allow the victim to rest. Assure fresh air breathing. : Remove affected clothing and wash all exposed skin area with mild soap and - Skin contact water, followed by warm water rinse. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed. - Eye contact : Check for and remove contact lenses. Ensure adequate flushing of eyes by separating eyelids with the fingers. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist. : Rinse mouth. Do not induce vomiting. - Ingestion If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Vomitting after ingestion may cause aspiration into the lungs, which may cause severe lungdamage or death. Never give anything by mouth to an unconscious person. : Treat symptomatically. Note to physician

#### **5 FIRE-FIGHTING MEASURES**

Specific hazards Hazardous combustion products	<ul> <li>When exposed to heat, may decompose liberating hazardous gases.</li> <li>Metal oxides.</li> <li>CO, CO2, POx, NOx, SOx, H2S.</li> <li>Under fire conditions, hazardous fumes will be present.</li> </ul>
- Suitable extinguishing media	: Water fog. Dry powder. Carbon dioxide. Foam.
- Unsuitable extinguishing media	: Do not use a heavy water stream.
Surrounding fires	: Use water spray or fog for cooling exposed containers.
Special procedures	: Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter environment.

Revision: 4 October 2009

SDS No. V161500030

Version number: 1

Page 3 of 7



#### 5 FIRE-FIGHTING MEASURES (continued)

**Special protective equipment for fire** : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

#### **6 ACCIDENTAL RELEASE MEASURES**

Personal precautions	<ul> <li>When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.</li> <li>Spill area may be slippery.</li> <li>Equip cleanup crew with proper protection.</li> </ul>
Environmental precautions	<ul> <li>Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.</li> <li>Recover the cleaning water for later dis posal. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.</li> </ul>
Clean up methods	: Take up large spills with pump or vacuum. Absorb with liquid-binding material ( sand, diatomite, acid binders, universal binders, sawdust).
- on water	: On water, recover/skim from surface and pour out in disposal container.
- on soil	<ul> <li>Clean up any spills as soon as possible, using an absorbent material to collect it. Use suitable disposal containers.</li> </ul>
Contaminated product, soil, water	: Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

#### 7 HANDLING AND STORAGE

General Precautions in handling and storage	<ul> <li>Handle in accordance with good industrial hygiene and safety procedures.</li> <li>Avoid contact with skin and eyes.</li> </ul>
Storage	<ul> <li>Always keep in containers of same material as the original one.</li> <li>Do not store in open or unlabelled containers.</li> <li>Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.</li> </ul>
Storage life	: 5 years.
Storage - away from	: Strong oxidizing agents. Strong acids.
Handling	<ul> <li>Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.</li> <li>Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.</li> <li>Wash clothing before re-using.</li> <li>Where contact with eyes or skin is likely, wear suitable protection.</li> </ul>

#### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits	: Exposure-value for oil mist: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).
Industrial hygiene	: Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands.
	Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.

Revision: 4 October 2009

SDS No. V161500030

Version number: 1

Page 4 of 7



#### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

- Respiratory protection	Wh : Res natu Wh prot Res time Pro can A co 65°C	sh clothing before re-using. en using, do not eat, drink or s piratory protective equipment i ural or local exhaust ventilation ere excessive vapour, mist, or ection equipment. piratory protective equipment i e it is worn. vided an air-filtering/air-purifyin be used for mist or fume. Use ombination filter for particles ar C) may be required if vapour of	is not normally required to control exposur dust may result, us must be checked to g respirator is suita filter type P or con not organic gases a r abnormal odour is	e. se approved respiratory o ensure it fits correctly each able, a filter for particulates nparable standard. nd vapours (boiling point > s also present due to high
- Hand protection	: In c : In c The is re The	<ul> <li>product temperature. Use filter type AP or comparable standard.</li> <li>In case of repeated or prolonged contact wear gloves.</li> <li>The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).</li> <li>The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).</li> </ul>		
Material	Thickness (mm)	Breakthrough time (min)	Level	according
Nitril.	0.4	480	6	EN 374
Neoprene.(chloroprene)	0.65	60	3	EN 374
- Eye protection	Eye	ety glasses with side shields. E protection should only be nec ayed.		
- Skin protection	con Avo If re	special clothing/skin protection ditions of use. id repeated or prolonged skin peated skin contact or contam uld be worn.	contact.	
Environmental Exposure Controls		Heading 6. See Heading 12.		

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C	: Oily liquid.
Colour	: Amber.
Odour	: Characteristic.
Pour point [°C]	: < -36
Boiling point [°C]	: > 280
Density (kg/l) @ 20 °C	: 0.85
Vapour pressure [kPa @20°C]	: < 0.01
Relative vapour density (air=1)	: > 1
Viscosity at 40°C [mm2/s]	: 50 - 150
Viscosity at 20°C [mm2/s]	: 100 - 300
Solubility in water	: Not miscible with water.
Flash point [°C]	: > 200
Auto-ignition temperature [°C]	: > 240
Explosion limits - lower [%]	: 0.6
Explosion limits - upper [%]	: 7

9 PHYSICAL AND CHEMICAL PROPERTIES (continued)

## **SAFETY DATA SHEET**

Revision: 4 October 2009

SDS No. V161500030

Version number: 1

Page 5 of 7



Log P octanol / water at 20°C	: > 3		
Evaporation rate (BuAc=1)	: < 0.1		
0 STABILITY AND REACTIVITY			
Stability and reactivity	: Stable under normal conditions.		
Hazardous decomposition products	: On exposure to high temperature, may decompose, releasing toxic/flammable		
	vapours. CO, CO2, POx, NOx, SOx, H2S. Metal oxides.		
Hazardous reactions	: None under normal conditions.		
Hazardous polymerization	: Will not occur.		
Materials to avoid	: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.		
Conditions to avoid	: See Heading 6. See Heading 7. See Heading 15.		
11 TOXICOLOGICAL INFORMATION			
Basis for Assessment	: Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology similar products.		
Toxicokinetics, metabolism and distribution	: No data available.		
Acute effects (acute toxicity, irritation and corrosivity)	n		
- Acute toxicity	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.		
On product			
- Irritation	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.		
- Corrosivity	: No data available.		
CMR effects			
- Carcinogenity	: Unknown.		
- Mutagenicity	: Unknown.		
- Reproductive and Developmental Toxicity	: Unknown.		
Repeated dose toxicity	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. Repeated dermal contact with material can lead to defatting of the skin.		
- Other	: The base oil contains less than 3% DMSO-extract measured according IP 346, therefor it is NOT classified as T/R45: "May cause cancer" (Note L). High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.		

Revision: 4 October 2009

SDS No. V161500030

Version number: 1

Page 6 of 7



12 ECOLOGICAL INFORMATION		
<ul> <li>Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.</li> </ul>		
: This product floats on water and may affect the oxygen-balance in the water.		
: No data available.		
: This product is not expected to bioaccumulate through food chains in the environment.		
: Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.		
: None.		
: Not miscible with water.		
Spillages may penetrate the soil causing ground water contamination.		
: Unknown.		
: Unknown.		

#### **13 DISPOSAL CONSIDERATIONS**

General	: Avoid release to the environment. Dispose of this material and its container at hazardous or special waste collection point. Dispose in a safe manner in accordance with local/national regulations.
Industrial waste number	<ul> <li>13 02 06 - Synthetic engine, gear and lubricating oils. (Hazardous waste pursuant to Directive 91/689/EEC on hazardous waste)</li> </ul>
Contaminated packaging	<ul> <li>Dispose in a safe manner in accordance with local/national regulations.</li> <li>Dispose of this material and its container at hazardous or special waste collection point.</li> </ul>
Special precautions	<ul> <li>After use, this oil must be sent to a used oil collecting location. Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden.</li> <li>Incorrect disposal of used oil endangers the environment. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.</li> <li>When not empty dispose of this container at hazardous or special waste collection point.</li> </ul>
14 TRANSPORT INFORMATION	

General information

: Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

### 15 REGULATORY INFORMATION

EC Classification

: This preparation is not classified as dangerous according to Directive 1999/45/EC as amended and adapted.

Revision: 4 October 2009

SDS No. V161500030

Page 7 of 7

Version number: 1



15 REGULATORY INFORMATION (continued)		
Symbol(s)	: None.	
R Phrase(s)	: None.	
S Phrase(s)	: None.	
Further Phrases	: Safety data sheet available for professional user on request.	
<ul> <li>National provisions</li> </ul>		
Germany	: WGK (Water-endangermant class) : 2	
16 OTHER INFORMATION		
Recommended uses and restrictions	: Specifications and technical informations on the product may be obtained by your dealer.	
List of relevant R phrases (heading 3)	<ul> <li>R23/24/25 : Toxic by inhalation, in contact with skin and if swallowed.</li> <li>R33 : Danger of cumulative effects.</li> <li>R38 : Irritating to skin.</li> <li>R41 : Risk of serious damage to eyes.</li> <li>R50/53 : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</li> <li>R51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</li> <li>R62 : Possible risk of impaired fertility.</li> </ul>	

The contents and format of this SDS are in accordance with REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document