



Revision: 2 October 2009 SDS No. V161500031 Version number: 1

#### IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier ENEOS PREMIUM HYPER 5W40** 1.1

1.2 Use Synthetic engine oil.

1.3 Details of the supplier of

the safety data sheet

JX Nippon Oil & Energy Europe Limited.

4th Floor, 4 Moorgate, London EC2R 6DA, U.K.

1.4 Telephone number +44-20-7186-0400

1.5 **FAX** number +44-20-7186-0419

### 2 HAZARDS IDENTIFICATION

: The classification is according to the latest editions of the EU-lists, and extended by Classification system

company and literature data.

: This preparation is not classified as dangerous according to Directive 1999/45/EC Hazard classification

as amended and adapted.

Other hazards

Human health hazards : Prolonged or repeated contact may cause skin to become dry or cracked.

Physical/chemical hazards

**Environmental hazards** : This product floats on water and may affect the oxygen-balance in the water.

Primary route of exposure

Effects and symptoms

- Inhalation : At normal ambient temperatures this product will be unlikely to present an

inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products

occurs.

: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or - Skin contact

repeated exposure may lead to dermatitis.

High-pressure injection under skin may cause serious damage.

: Skin and eyes contact.

: Unlikely to cause more than transient stinging or redness if accidental eye contact - Eye contact

occurs.

: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though - Ingestion

larger quantities may cause nausea and diarrhoea.

: USED ENGINE OILS: Used engine oil may contain hazardous components which Note

have the potential to cause skin cancer. See Toxicological Information, section 11 of

this Safety Data Sheet.

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

: Preparation. Substance / Preparation

SDS No. V161500031 Version number: 1



## 3 COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Chemical characterization

: Chemically modified base oil and proprietary performance additives.

Components

Revision: 2 October 2009

: This product is not hazardous but contains hazardous components.

Composition

Substances presenting a health or environmental hazard within the meaning of Directive 67/548/EEC / Substances for which there are Community workplace

exposure limits:

Substance name		Conc. (wt%)	CAS No	EC No	Annex No	Classification
Calcium Long Chain alkyl salicylate	:	Between 1 and 5 %				 R52-53
Zinc alkyl dithiophosphate	:	Between 1 and 5 %	68649-42-3	272-028-3		 Xi; R38-41 N; R51-53

Other information

: Occupational Exposure Limit(s), if available, are listed in section 8.

The base oil contains less than 3% DMSO-extract measured according IP 346,

therefor it is NOT classified as T/R45: "May cause cancer" (Note L).

**Text of R-Phrases** : See Heading 16.

### **4 FIRST AID MEASURES**

- General information

: Seek medical attention if ill effect develops.

- Inhalation

: Allow the victim to rest. Assure fresh air breathing.

- Skin contact

: Remove affected clothing and wash all exposed skin area with mild soap and

water, followed by warm water rinse.

High pressure injection of product into the skin may lead to local necrosis if the

product is not surgically removed.

- Eye contact

: Check for and remove contact lenses.

Ensure adequate flushing of eyes by separating eyelids with the fingers. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or

redness persist.

- Ingestion

: Rinse mouth. Do not induce vomiting.

If vomiting occurs spontaneously, keep head below the hips to prevent aspiration. Vomitting after ingestion may cause aspiration into the lungs, which may cause

severe lungdamage or death.

Never give anything by mouth to an unconscious person.

Note to physician : Treat symptomatically.

### **5 FIRE-FIGHTING MEASURES**

Specific hazards

: When exposed to heat, may decompose liberating hazardous gases.

**Hazardous combustion products** 

: Metal oxides

CO, CO2, POx, NOx, SOx, H2S.

Under fire conditions, hazardous fumes will be present.

- Suitable extinguishing media

: Water fog. Dry powder. Carbon dioxide. Foam.

- Unsuitable extinguishing media

: Do not use a heavy water stream.

Surrounding fires

: Use water spray or fog for cooling exposed containers.

Special procedures Avoid (reject) fire-fighting water to enter environment.

: Exercise caution when fighting any chemical fire.

Special protective equipment for fire

Do not enter fire area without proper protective equipment, including respiratory

fighters

protection. Use self-contained breathing apparatus.

Revision: 2 October 2009 SDS No. V161500031 Version number: 1



#### **6 ACCIDENTAL RELEASE MEASURES**

Personal precautions : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is

a risk of splashing) then chemical resistant aprons and/or impervious chemical

suits and boots will be required. Spill area may be slippery.

Equip cleanup crew with proper protection.

**Environmental precautions** : Stop the flow of material, if possible without risk. Dike spilled material, where this is

possible

Recover the cleaning water for later dis

posal. Prevent entry to sewers and public waters. Notify authorities if product enters

sewers or public waters.

Clean up methods : Take up large spills with pump or vacuum. Absorb with liquid-binding material (

sand, diatomite, acid binders, universal binders, sawdust).

- on water : On water, recover/skim from surface and pour out in disposal container.

- on soil : Clean up any spills as soon as possible, using an absorbent material to collect it.

Use suitable disposal containers.

Contaminated product, soil, water : Sweep up and remove to a suitable, clearly marked container for disposal in

accordance with local regulations.

#### 7 HANDLING AND STORAGE

**General** : Handle in accordance with good industrial hygiene and safety procedures.

Precautions in handling and storage : Avoid contact with skin and eyes.

Storage : Always keep in containers of same material as the original one.

Do not store in open or unlabelled containers.

Store in tightly closed, properly ventilated containers away from heat, sparks, open

flame.

Storage life : 5 years.

Storage - away from : Strong oxidizing agents. Strong acids.

Handling : Empty containers retain product residue (solid, liquid, and/or vapor) and can be

dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or

disposed of properly.

Wash hands and other exposed areas with mild soap and water before eat, drink or

smoke and when leaving work. Wash clothing before re-using.

Where contact with eyes or skin is likely, wear suitable protection.

#### **8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Occupational Exposure Limits : Exposure-value for oil mist: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

**Industrial hygiene** : Do not put the product-soaked rags into the pockets of working clothes.

Do not use cloths stained with the product to dry hands.

Week hands and the name and areas with wild as an a

Wash hands and other exposed areas with mild soap and water before eat, drink or

smoke and when leaving work. Wash clothing before re-using.


When using, do not eat, drink or smoke.

- Respiratory protection : Respiratory protective equipment is not normally required where there is adequate

natural or local exhaust ventilation to control exposure.

Where excessive vapour, mist, or dust may result, use approved respiratory

protection equipment.





## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Respiratory protective equipment must be checked to ensure it fits correctly each

time it is worn.

Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates

can be used for mist or fume. Use filter type P or comparable standard. A combination filter for particles and organic gases and vapours (boiling point > 65°C) may be required if vapour or abnormal odour is also present due to high

product temperature. Use filter type AP or comparable standard.

- Hand protection : In case of repeated or prolonged contact wear gloves.

The gloves should be replaced immediately in case of damage or signs of wear. It

is recommended to use preventative skin protection (skin cream).

The protection glove should be tested for its specific suitability (e.g. mechanical

strength, product compatibility, anti-static properties).

Material	Thickness (mm)	Breakthrough time (min)	Level	according
Nitril.	0.4	480	6	EN 374
Neoprene.(chloroprene)	0.65	60	3	EN 374

- Eye protection : Safety glasses with side shields. Equipment should conform to EN 166.

Eye protection should only be necessary where liquid could be splashed or

sprayed

- Skin protection : No special clothing/skin protection equipment is recommended under normal

conditions of use.

Avoid repeated or prolonged skin contact.

If repeated skin contact or contamination of clothing is likely, protective clothing

should be worn.

**Environmental Exposure Controls**: See Heading 6. See Heading 12.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C : Oily liquid.
Colour : Amber.

Odour : Characteristic.

 Pour point [°C]
 : < -39</td>

 Boiling point [°C]
 : > 280

 Density (kg/l) @ 20 °C
 : 0.85

 Vapour pressure [kPa @20°C]
 : < 0.01</td>

 Relative vapour density (air=1)
 : > 1

 Viscosity at 40°C [mm2/s]
 : 50 - 150

 Viscosity at 20°C [mm2/s]
 : 150 - 300

Solubility in water : Not miscible with water.

Flash point [°C] : > 200
Auto-ignition temperature [°C] : > 240
Explosion limits - lower [%] : 0.6
Explosion limits - upper [%] : 7
Log P octanol / water at 20°C : > 3
Evaporation rate (BuAc=1) : < 0.1

Version number: 1



#### 10 STABILITY AND REACTIVITY

Revision: 2 October 2009

Stability and reactivity : Stable under normal conditions.

Hazardous decomposition products : On exposure to high temperature, may decompose, releasing toxic/flammable

vapours.

SDS No. V161500031

CÓ, CO2, POx, NOx, SOx, H2S. Metal oxides.

**Hazardous reactions** : None under normal conditions.

Hazardous polymerization : Will not occur.

Materials to avoid : May react with strong acids or strong oxidizing agents, such as chlorates, nitrates,

peroxides, etc.

Conditions to avoid : See Heading 6. See Heading 7. See Heading 15.

#### 11 TOXICOLOGICAL INFORMATION

Basis for Assessment : Toxicological data have not been determined specifically for this product.

Information given is based on a knowledge of the components and the toxicology of

similar products.

Toxicokinetics, metabolism and

distribution

: No data available.

Acute effects (acute toxicity, irritation

and corrosivity)

- Acute toxicity : At normal ambient temperatures this product will be unlikely to present an

inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products

occurs.

--On product

- Irritation : Unlikely to cause more than transient stinging or redness if accidental eye contact

occurs

- Corrosivity : No data available.

**CMR** effects

- Carcinogenity : Unknown.- Mutagenicity : Unknown.

- Reproductive and Developmental

Toxicity

: Unknown.

Repeated dose toxicity : Unlikely to cause harm to the skin on brief or occasional contact but prolonged or

repeated exposure may lead to dermatitis.

Repeated dermal contact with material can lead to defatting of the skin.

- Other : The base oil contains less than 3% DMSO-extract measured according IP 346,

therefor it is NOT classified as T/R45: "May cause cancer" (Note L).

High pressure injection of product into the skin may lead to local necrosis if the

product is not surgically removed.

#### 12 ECOLOGICAL INFORMATION

Basis for Assessment : Ecotoxicological data have not been determined specifically for this product.

Information given is based on a knowledge of the components and the

ecotoxicology of similar products.

**Ecological effects information** 

On product : This product floats on water and may affect the oxygen-balance in the water.

**Ecotoxicity** : No data available.

Revision: 2 October 2009 SDS No. V161500031 Version number: 1



## 12 ECOLOGICAL INFORMATION (continued)

--On product

Bioaccumulative potential : This product is not expected to bioaccumulate through food chains in the

environment.

: Major constituents are expected to be inherently biodegradable, but the product Persistence - degradability

contains components that may persist in the environment.

VOC -(g/I)

(Volatile organic compounds)

: None.

Mobility

: Not miscible with water.

Spillages may penetrate the soil causing ground water contamination.

Results of PBT assessment

: Unknown.

Other Adverse Effects

: Unknown.

### 13 DISPOSAL CONSIDERATIONS

: Avoid release to the environment. Dispose of this material and its container at General

hazardous or special waste collection point. Dispose in a safe manner in

accordance with local/national regulations.

: 13 02 06 - Synthetic engine, gear and lubricating oils. (Hazardous waste pursuant Industrial waste number

to Directive 91/689/EEC on hazardous waste)

Contaminated packaging : Dispose in a safe manner in accordance with local/national regulations.

Dispose of this material and its container at hazardous or special waste collection

**Special precautions** : After use, this oil must be sent to a used oil collecting location.

Every mixture with foreign substances such as solvents, brake- and cooling liquids

is forbidden.

Incorrect disposal of used oil endangers the environment.

Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or

disposed of properly.

When not empty dispose of this container at hazardous or special waste collection

point.

#### 14 TRANSPORT INFORMATION

**General information** : Not classified as hazardous for transport (ADR/RID, ADNR, IMDG, ICAO/IATA)

## 15 REGULATORY INFORMATION

**EC Classification** : This preparation is not classified as dangerous according to Directive 1999/45/EC

as amended and adapted.

Symbol(s) : None. : None. R Phrase(s) S Phrase(s)

: Safety data sheet available for professional user on request. **Further Phrases** 

National provisions

SDS No. V161500031 Version number: 1



## 15 REGULATORY INFORMATION (continued)

Germany : WGK (Water-endangermant class) : 2

## **16 OTHER INFORMATION**

Revision: 2 October 2009

Recommended uses and restrictions : Specifications and technical informations on the product may be obtained by your

dealer.

List of relevant R phrases (heading 3): R38: Irritating to skin.

R41: Risk of serious damage to eyes.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

The contents and format of this SDS are in accordance with REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

**End of document**