

EU00050

ENEOS Super Plus 15W40

Mixed-fleet Motor Oil

ENEOS Super Plus 15W40 is universal Engine Oil developed to conform to the variety of oil and exhaust emissions requirements, for viscosity increase and wear. It has an excellent cleaning ability. It is especially suitable for mixed fleet applications, like gasoline, LPG and Diesel engines, with or without turbochargers and/or catalytic converter. In addition, this oil also fulfills the strict norms concerning deposits on the piston crown, the upper piston-ring groove and the rest of the pistons and exceeds the demands of manufacturers in the automotive sector.

● SPECIAL FEATURES

1. Reduced Oil Stock Level

Universal multi-fleet oil blended with the carefully selected formulation for broad applications in gasoline, LPG and diesel engines. This oil benefits to reduce the oil stock space considerably at the wholesaler or fleet-owner.

2. Excellent Resistance to Wear, Corrosion, Foaming and Oxidation

This oil gives optimum protection against wear and has anti-corrosion and anti-foam characteristics as well as a high resistance against oxidation.

● PERFORMANCE LEVEL

- API: CG-4/CF-4/CF/SJ
- ACEA: A2/B3/E2/A3
- VW 501/505
- MB: 228.1, 229.1
- Volvo: VDS
- MAN: 271
- Mack: EO/-L

● APPLICATION

- Motor oil for mixed fleet applications, like gasoline, LPG and Diesel engines, with or without turbo and/or catalytic converter
- Motor oil for off-highway applications, e.g: construction & agricultural equipments

● CONTAINERS

1L, 4L, 18L, 200L, 1000 IBC

● TYPICAL PROPERTIES

SAE viscosity grade	15W-40
Density (20°C), g/cm ³	0.879
Flash point (COC), °C	215
Kinematic viscosity (40°C), mm ² /s	102.5
(100°C), mm ² /s	13.9
Viscosity index	137
Pour point, °C	-27.0

Note: The typical properties may be changed without notice.
(February 2006)

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE.